



# AGS-II

## PRODUCT INFORMATION

- ✓ OIML Class III version, standard IP68 and set as Dual interval.\*\*
- ✓ Higher weighing precision possible for internal use.
- ✓ IP66 and IP68 construction, ideal in humid environments.
- ✓ Moisture-repellent silicone coating that protects the electronics
- ✓ IR sensor for hands-free operation of tare, zero or M+, efficient and hygienic.
- ✓ Durable mechanical keys.
- ✓ Smart Lock offers three different modes for versatile applications.
- ✓ Advanced tare options, continuous, automatic and packaging options.
- ✓ 19mm large LCD display digits, with audible buzzer feedback.
- ✓ Weighing stability filter, Check weighing (Low-OK-High) I.C.M. 3 color display
- ✓ Automatic calibration and gravity settings
- ✓ Built-in real-time clock (RTC), ideal for data output.
- ✓ Loadcell protected against overload.
- ✓ Power source: AC100~240 V, DC 12V / 0.5A, built-in rechargeable battery: DC6V 4Ah
- ✓ Operating temperature: -10°C / 40°C (14°F / 104°F), R.H. 85%
- ✓ Options: RS-232 - Wi-Fi - Bluetooth
- ✓ Platter size: AGS-II 300/600 g = Ø150 mm, other AGS-II models = 210 x 210 mm



MODEL	CAPACITY	READABILITY
AGS-II	300 g	0,1 g
AGS-II	600 g	0,2 g
AGS-II	3/6 kg	1/2 g
AGS-II	6/15 kg	5/10 g
AGS-II	15/30 kg	5/10 g

\*\* AGS-II 300 and 600g (IP66) are single range as standard.

