



## PRODUCT INFORMATION

- ✓ OIML R76:2006 Approved in Compliance with EN45501:2015 and NAWI directive 2014/31/EU
- ✓ High Speed 24 bits Multiplexed Delta-Sigma A/D Converters for Performance and Stability
- ✓ Support Unit Price Base as per kg or per 100g
- ✓ Wide Angle LCD Display with LED Backlight
- ✓ Compact Design for Space Efficiency
- ✓ Overload and Shock Protection Mechanism Protects against Excessive Loads and Shock
- ✓ Easy Grip Design for Mobility Convenience
- ✓ Functions Including: Power On Zero Tracking, Manual Zero, Full Subtractive Tare, Memory Accumulation, Non-Weigh Article, Fixed Unit Price, Paid & Change, Auto Power Saving, Low Battery Warning and Charging Status Indicator, Auto Power Saving, Low Battery Warning and Charging Status Indicator
- ✓ Backlight and Dual Side Display included
- ✓ Rechargeable Battery, Power Adaptor, Adjustable Feet
- ✓ Long Battery Operation Time: 200 Hours Plus
- ✓ Platter size: 230 x 250 mm
- ✓ Options available: RS-232 Interface







Model	Capacity	Readability
VGP-3	1.5 / 3 kg	0.5 / 1 g
VGP-6	3 / 6 kg	1/2g
VGP-15	6 / 15 kg	2/5g
VGP-30	15 / 30 kg	5 / 10 g



